

## **In the Claims**

### **Claims pending**

- At time of the Action: Claims 1-37.
- After this Response: Claims 1-37.

**Currently Amended Claims:** None.

**Currently Canceled claims:** None.

**1. (Original)** A method for open content model Web service messaging in a networked computing environment, the method comprising:

generating a transport neutral message comprising message recipient, endpoint addressing information, and one or more reference properties comprising selectively opaque message context;

binding the transport neutral message to a transport protocol for communication to the message recipient; and

wherein at least a portion of the selectively opaque message context is not directed to the message recipient.

**2. (Original)** A method as recited in claim 0, wherein the selectively opaque context directs an endpoint to send one or more responses to a message source, the message source not being the message recipient.

3. **(Original)** A method as recited in claim 0, wherein a portion of the selectively opaque context directs the message recipient as to how to handle one or more messages sent to the endpoint in a session.
4. **(Original)** A method as recited in claim 0, wherein the message recipient is a service coordinator.
5. **(Original)** A method as recited in claim 0, wherein the selectively opaque message context is based on an Extended Markup Language (XML) messaging protocol.
6. **(Original)** A method as recited in claim 0, wherein binding, the transport protocol is based on Simple Object Access Protocol (SOAP).
7. **(Original)** A method as recited in claim 0, wherein the addressing information and selectively opaque message context are respectfully specified by an endpoint reference and message information headers.
8. **(Original)** A method as recited in claim 7, wherein the endpoint reference is self-contained service endpoint description.
9. **(Original)** A method as recited in claim 7, wherein the endpoint reference and/or message information headers provide identification and description of specific service instances and/or specific instance details.

**10. (Original)** A method as recited in claim 7, wherein the message information headers further comprise a reply to property identifying an intended recipient for a reply to the transport neutral message, a relates to property that indicates how the transport neutral message relates to a different transport neutral message.

**11. (Original)** A computer-readable medium comprising computer-program instructions for open content model Web service messaging in a networked computing environment, the computer-program instructions being executable by a processor for:

generating a transport neutral message comprising message recipient, endpoint addressing information, and one or more reference properties comprising selectively opaque message context;

binding the transport neutral message to a transport protocol for communication to the message recipient; and

wherein at least a portion of the selectively opaque message context is not directed to the message recipient.

**12. (Original)** A computer-readable medium as recited in claim 11, wherein the selectively opaque context directs an endpoint to send one or more responses to a message source, the message source not being the message recipient.

**13. (Original)** A computer-readable medium as recited in claim 11, wherein a portion of the selectively opaque context directs the message recipient as to how to handle one or more messages sent to the endpoint in a session.

**14. (Original)** A computer-readable medium as recited in claim 11, wherein the message recipient is a service coordinator.

**15. (Original)** A computer-readable medium as recited in claim 11, wherein the selectively opaque message context is based on an Extended Markup Language (XML) messaging protocol.

**16. (Original)** A computer-readable medium as recited in claim 11, wherein binding, the transport protocol is based on Simple Object Access Protocol (SOAP).

**17. (Original)** A computer-readable medium as recited in claim 11, wherein the addressing information and selectively opaque message context are respectfully specified by an endpoint reference and message information headers.

**18. (Original)** A computer-readable medium as recited in claim 17, wherein the endpoint reference is self-contained service endpoint description.

**19.** A computer-readable medium as recited in claim 17, wherein the endpoint reference and/or message information headers provide identification and description of specific service instances and/or specific instance details.

**20. (Original)** A computer-readable medium as recited in claim 17, wherein the message information headers further comprise a reply to property identifying an intended recipient for a reply to the transport neutral message, a relates to property that indicates how the transport neutral message relates to a different transport neutral message.

**21. (Original)** A computing device comprising:

a processor; and

a memory coupled to the processor, the memory comprising computer-program instructions executable by the processor for open content model messaging in a networked computing environment, the computer-program instructions comprising instructions for:

generating a transport neutral message comprising message recipient, endpoint addressing information, and one or more reference properties comprising selectively opaque message context;

binding the transport neutral message to a transport protocol for communication to the message recipient; and

wherein at least a portion of the selectively opaque message context is not directed to the message recipient.

**22. (Original)** A computing device as recited in claim 21, wherein the selectively opaque context directs an endpoint to send one or more responses to a message source, the message source not being the message recipient.

**23. (Original)** A computing device as recited in claim 21, wherein a portion of the selectively opaque context directs the message recipient as to how to handle one or more messages sent to the endpoint in a session.

**24. (Original)** A computing device as recited in claim 21, wherein the message recipient is a service coordinator.

**25. (Original)** A computing device as recited in claim 21, wherein the selectively opaque message context is based on an Extended Markup Language (XML) messaging protocol.

**26. (Original)** A computing device as recited in claim 21, wherein binding, the transport protocol is based on Simple Object Access Protocol (SOAP).

**27. (Original)** A computing device as recited in claim 21, wherein the addressing information and selectively opaque message context are respectfully specified by an endpoint reference and message information headers.

**28. (Original)** A computer computing device as recited in claim 27, wherein the endpoint reference is self-contained service endpoint description.

**29. (Original)** A computing device as recited in claim 27, wherein the endpoint reference and/or message information headers provide identification and description of specific service instances and/or specific instance details.

**30. (Original)** A computer-readable medium as recited in claim 17, wherein the message information headers further comprise a reply to property identifying an intended recipient for a reply to the transport neutral message, a relates to property that indicates how the transport neutral message relates to a different transport neutral message.

**31. (Original)** A computing device comprising:

means for generating a transport neutral message comprising message recipient, endpoint addressing information, and one or more reference properties comprising selectively opaque message context;

means for binding the transport neutral message to a transport protocol for communication to the message recipient; and

wherein at least a portion of the selectively opaque message context is not directed to the message recipient.

**32. (Original)** A computing device as recited in claim 31, wherein the selectively opaque context directs an endpoint to send one or more responses to a message source, the message source not being the message recipient.

**33. (Original)** A computing device as recited in claim 31, wherein a portion of the selectively opaque context directs the message recipient as to how to handle one or more messages sent to the endpoint in a session.

**34. (Original)** A computing device as recited in claim 31, wherein the message recipient is a service coordinator.

**35. (Original)** A computer-readable medium comprising an open content model data structure thereon, the open content model data structure comprising:

a message recipient data field;

an endpoint addressing data field;

and one or more reference properties data fields comprising selectively opaque message context, at least a portion of the selectively opaque message context is not directed to the message recipient.

**36. (Original)** A computer-readable medium as recited in claim 34, wherein the selectively opaque context directs an endpoint to send one or more responses to a message source, the message source not being the message recipient.

**37. (Original)** A computer-readable medium as recited in claim 34, wherein a portion of the selectively opaque context directs the message recipient as to how to handle one or more messages sent to the endpoint in a session.